

DT-1S2AB-1SC

PINOUT DIAGRAM

STATUS INDICATORS

1. POWER (GREEN)
2. NA

STATUS INDICATORS

1. TX CARRIER (GREEN)/ERROR (RED)

S-VIDEO INPUT


STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

OPTICAL PORT OUT SC

AUDIO INPUT (PORT 4) (DB-9 FEMALE)

1. (CH.1) GND
2. (CH.1) INPUT
3. (CH.2) GND
4. (CH.2) INPUT
5. GND
6. NA
7. NA
8. NA
9. NA



STATUS INDICATORS (PORT 4)

1. (CH.1) AUDIO INPUT PRESENT
2. (CH.1) AUDIO INPUT OVERLOAD
3. (CH.2) AUDIO INPUT PRESENT
4. (CH.2) AUDIO INPUT OVERTLOAD
5. NA
6. NA
7. NA
8. NA

DR-1S2AB-1SC

PINOUT DIAGRAM

STATUS INDICATORS

1. POWER (GREEN)
2. NA


STATUS INDICATORS

1. NA

S-VIDEO OUTPUT

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)



STATUS INDICATORS

1. RX OPTICAL SIGNAL (GREEN)/ABSENT (RED)
2. NA
3. RX CARRIER (GREEN)/ERROR (RED)

OPTICAL PORT IN SC

STATUS INDICATORS (PORT 4)

1. (CH.1) AUDIO OUTPUT PRESENT
2. (CH.1) AUDIO OUTPUT OVERLOAD
3. (CH.2) AUDIO OUTPUT PRESENT
4. (CH.2) AUDIO OUTPUT OVERTLOAD
5. NA
6. NA
7. NA
8. NA

AUDIO OUTPUT (PORT 4) (DB-9 FEMALE)

1. NA
2. (CH.1) OUTPUT
3. NA
4. (CH.2) OUTPUT
5. GND
6. NA
7. NA
8. NA
9. NA