

DT-4V/8F-X

PINOUT DIAGRAM

STATUS INDICATORS

1. POWER (GREEN)
2. NA

STATUS INDICATORS

1. TX CARRIER (GREEN)/ERROR (RED)

VIDEO INPUT (CH.1)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

VIDEO INPUT (CH.3)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

DATA RS422 OUT (PORT 3)


(DB-9 FEMALE)

1. (CH.1) OUTPUT +
2. (CH.1) OUTPUT -
3. (CH.2) OUTPUT +
4. (CH.2) OUTPUT -
5. GND
6. (CH.3) OUTPUT +
7. (CH.3) OUTPUT -
8. (CH.4) OUTPUT +
9. (CH.4) OUTPUT -

DATA RS422 OUT (PORT 4)

(DB-9 FEMALE)

1. (CH.5) OUTPUT +
2. (CH.5) OUTPUT -
3. (CH.6) OUTPUT +
4. (CH.6) OUTPUT -
5. GND
6. (CH.7) OUTPUT +
7. (CH.7) OUTPUT -
8. (CH.8) OUTPUT +
9. (CH.8) OUTPUT -



OPTICAL PORT

STATUS INDICATORS

1. NA
2. RX OPTICAL SIGNAL (GREEN)/ABSENT (RED)
3. RX CARRIER (GREEN)/ERROR (RED)

VIDEO INPUT (CH.2)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

VIDEO INPUT (CH.4)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

STATUS INDICATORS (PORT 3)

1. NA
2. (CH.1) DATA OUTPUT
3. NA
4. (CH.2) DATA OUTPUT
5. NA
6. (CH.3) DATA OUTPUT
7. NA
8. (CH.4) DATA OUTPUT

STATUS INDICATORS (PORT 4)

1. NA
2. (CH.5) DATA OUTPUT
3. NA
4. (CH.6) DATA OUTPUT
5. NA
6. (CH.7) DATA OUTPUT
7. NA
8. (CH.8) DATA OUTPUT

DR-4V/8F-X

PINOUT DIAGRAM

STATUS INDICATORS

1. POWER (GREEN)
2. NA

STATUS INDICATORS

1. TX CARRIER (GREEN)/ERROR (RED)

VIDEO OUTPUT (CH.1)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

VIDEO OUTPUT (CH.3)

STATUS INDICATORS


1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

DATA RS422 IN (PORT 3) (DB-9 FEMALE)

1. (CH.1) INPUT +
2. (CH.1) INPUT -
3. (CH.2) INPUT +
4. (CH.2) INPUT -
5. GND
6. (CH.3) INPUT +
7. (CH.3) INPUT -
8. (CH.4) INPUT +
9. (CH.4) INPUT -

DATA RS422 IN (PORT 4) (DB-9 FEMALE)

1. (CH.5) INPUT +
2. (CH.5) INPUT -
3. (CH.6) INPUT +
4. (CH.6) INPUT -
5. GND
6. (CH.7) INPUT +
7. (CH.7) INPUT -
8. (CH.8) INPUT +
9. (CH.8) INPUT -



OPTICAL PORT

STATUS INDICATORS

1. NA
2. RX OPTICAL SIGNAL (GREEN)/ABSENT (RED)
3. RX CARRIER (GREEN)/ERROR (RED)

VIDEO OUTPUT (CH.2)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

VIDEO OUTPUT (CH.4)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

STATUS INDICATORS (PORT 3)

1. (CH.1) DATA INPUT
2. NA
3. (CH.2) DATA INPUT
4. NA
5. (CH.3) DATA INPUT
6. NA
7. (CH.4) DATA INPUT
8. NA

STATUS INDICATORS (PORT 4)

1. (CH.5) DATA INPUT
2. NA
3. (CH.6) DATA INPUT
4. NA
5. (CH.7) DATA INPUT
6. NA
7. (CH.8) DATA INPUT
8. NA