

DT-4V(W)*4F/4F-X

PINOUT DIAGRAM

STATUS INDICATORS

1. POWER (GREEN)
2. NA

STATUS INDICATORS

1. TX CARRIER (GREEN)/ERROR (RED)

VIDEO INPUT (CH.1)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

VIDEO INPUT (CH.3)

STATUS INDICATORS


1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

ATA RS422 INPUT (PORT 3) (DB-9 FEMALE)

1. (CH.1) INPUT
2. (CH.1) INPUT
3. (CH.2) INPUT
4. (CH.2) INPUT
5. GND
6. (CH.3) INPUT
7. (CH.3) INPUT
8. (CH.4) INPUT
9. (CH.4) INPUT

ATA RS422 OUTPUT (PORT 4) (DB-9 FEMALE)

1. (CH.1) OUTPUT
2. (CH.1) OUTPUT
3. (CH.2) OUTPUT
4. (CH.2) OUTPUT
5. GND
6. (CH.3) OUTPUT
7. (CH.3) OUTPUT
8. (CH.4) OUTPUT
9. (CH.4) OUTPUT



OPTICAL PORT

STATUS INDICATORS

1. NA
2. RX OPTICAL SIGNAL (GREEN)/ABSENT (RED)
3. RX CARRIER (GREEN)/ERROR (RED)

VIDEO INPUT (CH.2)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

VIDEO INPUT (CH.4)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

STATUS INDICATORS (PORT 3)

1. (CH.1) DATA INPUT
2. (CH.1) NA
3. (CH.2) DATA INPUT
4. (CH.2) NA
5. (CH.3) DATA INPUT
6. (CH.3) NA
7. (CH.4) DATA INPUT
8. (CH.4) NA

STATUS INDICATORS (PORT 4)

1. (CH.1) NA
2. (CH.1) DATA OUTPUT
3. (CH.2) NA
4. (CH.2) DATA OUTPUT
5. (CH.3) NA
6. (CH.3) DATA OUTPUT
7. (CH.4) NA
8. (CH.4) DATA OUTPUT

*V-8 BIT VIDEO

*W-10 BIT VIDEO

DR-4V(W)*4F/4F-X

PINOUT DIAGRAM

STATUS INDICATORS

1. POWER (GREEN)
2. NA

STATUS INDICATORS

1. TX CARRIER (GREEN)/ERROR (RED)

VIDEO OUTPUT (CH.1)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

VIDEO OUTPUT (CH.3)

STATUS INDICATORS


1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

ATA RS422 OUTPUT (PORT 3) (DB-9 FEMALE)

1. (CH.1) OUTPUT
2. (CH.1) OUTPUT
3. (CH.2) OUTPUT
4. (CH.2) OUTPUT
5. GND
6. (CH.3) OUTPUT
7. (CH.3) OUTPUT
8. (CH.4) OUTPUT
9. (CH.4) OUTPUT

DATA RS422 INPUT (PORT 4) (DB-9 FEMALE)

1. (CH.1) INPUT
2. (CH.1) INPUT
3. (CH.2) INPUT
4. (CH.2) INPUT
5. GND
6. (CH.3) INPUT
7. (CH.3) INPUT
8. (CH.4) INPUT
9. (CH.4) INPUT



OPTICAL PORT

STATUS INDICATORS

1. NA
2. RX OPTICAL SIGNAL (GREEN)/ABSENT (RED)
3. RX CARRIER (GREEN)/ERROR (RED)

VIDEO OUTPUT (CH.2)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

VIDEO OUTPUT (CH.4)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

STATUS INDICATORS (PORT 3)

1. (CH.1) NA
2. (CH.1) DATA OUTPUT
3. (CH.2) NA
4. (CH.2) DATA OUTPUT
5. (CH.3) NA
6. (CH.3) DATA OUTPUT
7. (CH.4) NA
8. (CH.4) DATA OUTPUT

STATUS INDICATORS (PORT 4)

1. (CH.1) DATA INPUT
2. (CH.1) NA
3. (CH.2) DATA INPUT
4. (CH.2) NA
5. (CH.3) DATA INPUT
6. (CH.3) NA
7. (CH.4) DATA INPUT
8. (CH.4) NA

*V-8 BIT VIDEO
*W-10 BIT VIDEO