

DT-AiphoneAX2-X

PINOUT DIAGRAM

STATUS INDICATORS

1. POWER (GREEN)
2. NA

STATUS INDICATORS

1. TX CARRIER (GREEN)/ERROR (RED)

VIDEO INPUT (CH.1)

STATUS INDICATORS


1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

AUDIO IN/OUT (PORT 3) (DB-9 FEMALE)

1. (CH.1) OUTPUT-
2. (CH.1) OUTPUT+
3. (CH.2) OUTPUT-
4. (CH.2) OUTPUT+
5. GND
6. (CH.1) INPUT-
7. (CH.1) INPUT+
8. (CH.2) INPUT-
9. (CH.2) INPUT+

DATA IN/OUT (PORT 4) (DB-15 FEMALE)

1. (CH.1) INPUT
2. (CH.2) INPUT
3. (CH.3) INPUT
4. (CH.4) INPUT
5. GND
6. (CH.1) OUTPUT
7. (CH.1) OUTPUT
8. (CH.2) OUTPUT
9. (CH.2) OUTPUT
10. (CH.3) OUTPUT
11. (CH.3) OUTPUT
12. (CH.4) OUTPUT
13. (CH.4) OUTPUT
14. NA
15. NA



OPTICAL PORT

STATUS INDICATORS

1. NA
2. RX OPTICAL SIGNAL (GREEN)/ABSENT (RED)
3. RX CARRIER (GREEN)/ERROR (RED)

VIDEO INPUT (CH.2)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

STATUS INDICATORS (PORT 3)

1. (CH.1) AUDIO INPUT PRESENT
2. (CH.1) AUDIO INPUT OVERLOAD
3. (CH.2) AUDIO INPUT PRESENT
4. (CH.2) AUDIO INPUT OVERLOAD
5. (CH.1) AUDIO OUTPUT PRESENT
6. (CH.1) AUDIO OUTPUT OVERLOAD
7. (CH.2) AUDIO OUTPUT PRESENT
8. (CH.2) AUDIO OUTPUT OVERLOAD

STATUS INDICATORS (PORT 4)

1. (CH.1) INPUT PRESENT
2. (CH.1) OUTPUT PRESENT
3. (CH.2) INPUT PRESENT
4. (CH.2) OUTPUT PRESENT
5. (CH.3) INPUT PRESENT
6. (CH.3) OUTPUT PRESENT
7. (CH.4) INPUT PRESENT
8. (CH.4) OUTPUT PRESENT

DR-AiphoneAX2-X

PINOUT DIAGRAM

STATUS INDICATORS

1. POWER (GREEN)
2. NA

STATUS INDICATORS

1. TX CARRIER (GREEN)/ERROR (RED)

VIDEO OUTPUT (CH.1)

STATUS INDICATORS


1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

AUDIO IN/OUT (PORT 3) (DB-9 FEMALE)

1. {CH.1} OUTPUT-
2. {CH.1} OUTPUT+
3. {CH.2} OUTPUT-
4. {CH.2} OUTPUT+
5. GND
6. {CH.1} INPUT-
7. {CH.1} INPUT+
8. {CH.2} INPUT-
9. {CH.2} INPUT+

DATA IN/OUT (PORT 4) (DB-15 FEMALE)

1. {CH.1} INPUT
2. {CH.2} INPUT
3. {CH.3} INPUT
4. {CH.4} INPUT
5. GND
6. {CH.1} OUTPUT
7. {CH.1} OUTPUT
8. {CH.2} OUTPUT
9. {CH.2} OUTPUT
10. {CH.3} OUTPUT
11. {CH.3} OUTPUT
12. {CH.4} OUTPUT
13. {CH.4} OUTPUT
14. NA
15. NA



OPTICAL PORT

STATUS INDICATORS

1. NA
2. RX OPTICAL SIGNAL (GREEN)/ABSENT (RED)
3. RX CARRIER (GREEN)/ERROR (RED)

VIDEO OUTPUT (CH.2)

STATUS INDICATORS

1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

STATUS INDICATORS (PORT 3)

1. {CH.1} AUDIO INPUT PRESENT
2. {CH.1} AUDIO INPUT OVERLOAD
3. {CH.2} AUDIO INPUT PRESENT
4. {CH.2} AUDIO INPUT OVERLOAD
5. {CH.1} AUDIO OUTPUT PRESENT
6. {CH.1} AUDIO OUTPUT OVERLOAD
7. {CH.2} AUDIO OUTPUT PRESENT
8. {CH.2} AUDIO OUTPUT OVERLOAD

STATUS INDICATORS (PORT 4)

1. {CH.1} INPUT PRESENT
2. {CH.1} OUTPUT PRESENT
3. {CH.2} INPUT PRESENT
4. {CH.2} OUTPUT PRESENT
5. {CH.3} INPUT PRESENT
6. {CH.3} OUTPUT PRESENT
7. {CH.4} INPUT PRESENT
8. {CH.4} OUTPUT PRESENT