


ST-1W2A-XD

PINOUT DIAGRAM

STATUS INDICATORS

DR1 - NA
 DR2 - NA
 AR1 - NA
 AR2 - NA
 CR1 - NA
 CR2 - NA
 DT1 - NA
 DT2 - NA
 AT1 - <CH.1> AUDIO INPUT
 AT2 - <CH.2> AUDIO INPUT
 CT1 - NA
 CT2 - NA



OPTICAL PORT (ST, FC)

STATUS INDICATORS

PWR - POWER (GREEN)
 DIAG - GREEN-OK, RED-ALARM
 TX C/L - TX CARRIER (GREEN) / OVERLOAD (RED)
 RX C/E - NA

VIDEO INPUT

STATUS INDICATORS

SYN - SYNC PRESENT (GREEN)
 VID - VIDEO PRESENT (GREEN) / OVERLOAD (RED)

AUDIO INPUT


1. <CH.1> AUDIO INPUT-
2. <CH.1> AUDIO INPUT+
3. <CH.2> AUDIO INPUT-
4. <CH.2> AUDIO INPUT+
5. GND

SR-1W2A-XD

PINOUT DIAGRAM

STATUS INDICATORS

DR1 - NA
 DR2 - NA
 AR1 - <CH.1> AUDIO OUTPUT
 AR2 - <CH.2> AUDIO OUTPUT
 CR1 - NA
 CR2 - NA
 DT1 - NA
 DT2 - NA
 AT1 - NA
 AT2 - NA
 CT1 - NA
 CT2 - NA



OPTICAL PORT (ST, FC)

STATUS INDICATORS

PWR - POWER (GREEN)
 DIAG - GREEN-OK, RED-ALARM
 TX C/L - NA
 RX C/E - RX CARRIER (GREEN) / ERROR (RED)

VIDEO OUTPUT

STATUS INDICATORS

SYN - SYNC PRESENT (GREEN)
 VID - VIDEO PRESENT (GREEN) / OVERLOAD (RED)

AUDIO OUTPUT

1. <CH.1> AUDIO OUTPUT-
2. <CH.1> AUDIO OUTPUT+
3. <CH.2> AUDIO OUTPUT-
4. <CH.2> AUDIO OUTPUT+
5. GND